

SAFETY DATA SHEET

GLAZE STRIP

Infosafe No.: LQ66J ISSUED Date : 04/06/2021 ISSUED by: JASOL AUSTRALIA

CLASSIFIED AS HAZARDOUS

Section 1 - Identification

Product Identifier

GLAZE STRIP

Product Code

2102380

Company Name

JASOL AUSTRALIA

Address

41-45 Tarnard Drive Braeside VIC 3195 AUSTRALIA

Telephone/Fax Number

Tel: 03 95805722 Fax: 03 95809902

Emergency Phone Number

1800 629953

Recommended use of the chemical and restrictions on use

Floor stripper

Other Information

Jasol (a division of George Weston Foods Limited) believes the information in this document to be accurate as at the date of preparation noted in the header of the SDS, but to the maximum extent permitted by law, Jasol accepts no responsibility for any loss or damage caused by any person acting or refraining from action because of this information.

The provision of this information should not be construed by anyone as a recommendation to use this product. In particular, no one should use any product in violation of any patent or other intellectual proprietary rights or in breach of any statute or regulation.

Users should rely on their own knowledge and inquiries and make their own determination as to the applicability of this information in relation to their particular purposes and specific circumstances. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace and in conjunction with other substances or products.

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Eye damage/irritation: Category 1 Flammable liquids: Category 4 Skin corrosion/irritation: Category 2

Signal Word (s) DANGER

Page 1 / 7

Hazard Statement (s)

H227 Combustible liquid.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Pictogram (s)

Corrosion



Precautionary Statement - Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P280 Wear protective gloves.

Precautionary Statement - Response

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see First Aid measures on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use Carbon dioxide, dry chemical or foam to extinguish.

Precautionary Statement - Storage

P403 Store in a well-ventilated place.

Precautionary Statement - Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

Section 3 - Composition and Information on Ingredients

Ingredients

Name	CAS	Proportion
Water	7732-18-5	60-100 %
2-Butoxyethanol	111-76-2	10-30 %
Ethanolamine	141-43-5	0-10 %
Ingredients determined not to be hazardous		Balance

Section 4 - First Aid Measures

Inhalation

If inhaled, remove affected person from contaminated area and keep at rest in a position comfortable for breathing. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Do NOT induce vomiting. Wash/rinse out mouth thoroughly with water. Seek immediate medical attention.

Skin

If on skin (or hair) remove/take off all contaminated clothing immediately after handling. Seek medical attention and wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. If skin irritation or rash occurs please advise medical physician.

Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses, if present and easy to do. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Product contains less than 15 % ethylene glycol monobutyl ether and less than 6% monoethanolamine. Vomiting has not been induced because of risk of aspiration into the lungs. Treat symptomatically. Contact Poisons Information Centre.

Most important symptoms/effects, acute, delayed and aggravated medical conditions

No adverse health effects expected if the product is handled in accordance with this MSDS and the product label. Symptoms that may arise if the product is mishandled are as follows:

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

Section 5 - Firefighting Measures

Suitable Extinguishing Media

Carbon dioxide, dry chemical or foam.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including water vapour, carbon dioxide and oxides of nitrogen. Incomplete combustion may generate carbon monoxide.

Specific hazards arising from the chemical

Combustible. This product will burn if exposed to fire.

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

Section 6 - Accidental Release Measures

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. As a water based product, if spilt on electrical equipment the product will cause short-circuits. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

Section 7 - Handling and Storage

Precautions for Safe Handling

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene by washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Protect from freezing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Storage Regulations

Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values

2-Butoxyethanol

TWA: 20 ppm, 96.9 mg/m³ STEL: 50 ppm, 242 mg/m³ (Sk)

Monoethanolamine TWA: 3 ppm, 7.5 mg/m³ STEL: 6 ppm, 15 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

Biological Monitoring

Name: 2-Butoxyethanol

Determinant: Butoxyacetic acid (BAA) in urine

Value: 200 mg/g creatinine Sampling time: End of shift

Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye and Face Protection

Safety glasses with full face shield should be used. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as rubber or plastic. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Page 4/7 Product Name: GLAZE STRIP

Section 9 - Physical and Chemical Properties

Properties	Description	Properties	Description
Form	Liquid	Appearance	Pink frothing liquid. Miscible with water in all proportions.
Colour	Pink	Odour	Low odour.
Melting Point	Not available	Boiling Point	> 80°C
Decomposition Temperature	Not available	Solubility in Water	Miscible with water in all proportions.
Specific Gravity	0.996	рН	11.4-12.9
Vapour Pressure	Not available.	Relative Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Partition Coefficient: n-octanol/water (log value)	Not available
Flash Point	>61°C	Flammability	Not flammable.
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available		

Section 10 - Stability and Reactivity

Reactivity

Reacts with incompatible materials

Chemical Stability

Stable under normal conditions of storage and handling.

Possibility of hazardous reactions

Not available

Conditions to Avoid

Heat, open flames and other sources of ignition

Incompatible Materials

Strong oxidising agents.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon dioxide and carbon monoxide.

Hazardous Polymerization

Not available

Section 11 - Toxicological Information

Toxicology Information

Toxicity data for material given below.

Acute Toxicity - Oral

LD50 2-Butoxy ethanol: 530-3000mg/kg oral, rat

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eve

Causes eye damage. Eye contact will cause stinging, blurring, tearing, severe pain and possible burns, necrosis, permanent damage and blindness.

Respiratory Sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ Cell Mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

2-Butoxyethanol is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT - Single Exposure

Not expected to cause toxicity to a specific target organ.

STOT - Repeated Exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

Other Information

Evidence from animal tests with 2-butoxy ethanol indicate that repeated or prolonged exposure to this chemical could result in liver, kidney, blood and central nervous system disorders.

Section 12 - Ecological Information

Ecotoxicity

No ecological data available for this material.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Prevent large amounts from entering waterways, drains and sewers.

Section 13 - Disposal Considerations

Disposal Considerations

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

Section 14 - Transport Information

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea

ADG U.N. Number

None Allocated

ADG Proper Shipping Name

None Allocated

ADG Transport Hazard Class

None Allocated

Special Precautions for User

Not available

IMDG Marine pollutant

Nο

Transport in Bulk

Not available

Section 15 - Regulatory Information

Regulatory Information

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule

S6

Section 16 - Any Other Relevant Information

Date of Preparation

SDS created: June 2016

Literature References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of classification and labelling of chemicals.

Contact Person/Point

The company has taken care in compiling this information. No liability is accepted whether direct or indirect from its application since the conditions of final use are outside the Company's control. The end user is obliged to conform to relevant government regulations and/or patent laws applicable in their respective States of Countries.

24-Hour Emergency Telephone: AUS: 1800 629 953 NZ: Poisons 0800 764 766, Spills 111 FIRE.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd. The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.